

www.grupponueva.com

Precious

Collection

by

GruppoNueva

one group - one mind - one vision

COLLECTION 2021

24 YEARS
1997 | 2021





Be a part of *Class*

when love and skill work together,

expect a *Masterpiece*

GruppoNueva

one group - one mind - one vision

One of the leading and emerging manufacturers, having headquarter in Morbi. Renowned for innovative ceramic excellence and a brand that stands for new thinking, Thinking that aligns with our client's need to serve them better. The group manufactures surfaces inspired by nature bringing in the warmth of natural elements with its color options and natural textures.

24^{YEARS}
1997 | 2021

nu
eva
PORCELAIN

nu
eva
MOSAICS

nu
eva
MARBLE

GRYPHON
PORCELAIN

CERAMICS
COSIA CERAMICS PVT LTD

GGCL
Gruppobrand



Precious
Collection

by

GruppoNueva

one group - one mind - one vision


COLLECTION 2021



simply dummy text of the printing and typesetting industry. Lorem Ipsum has been the industry's standard dummy text ever since the 1500s, when an unknown printer took a galley of type and scrambled it to make a type specimen book. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially

Unique 6 Design



Unique nature inspired collection with endless combinations. Subtle and strong colors with delicate veins that offers great aesthetics, lasting for decades.



-  **9mm** Thickness
-  **15mm** Thickness

Lusso tiles are durable with thickness of 9MM. The tiles are available in 1200x2400mm, 1200x1200mm, 600x1200mm and 600x600mm sizes making it apt for indoor applications.








BLUE OCEAN



BLUE OCEAN

Style that never goes out of fashion, and would perfectly enhance the interior space. The opulent feature gives high finish, gloss, and poise to your space.

Suitable
Applications

- 
MALL
- 
HALL
- 
HOTEL
- 
AIRPORT
- 
SPA



AVAILABLE SIZES
800x2400mm | 600x1200mm



Total Faces - 3










GEMSTONE GREEN



GEMSTONE GREEN

Style that never goes out of fashion, and would perfectly enhance the interior space. The opulent feature gives high finish, gloss, and poise to your space.

Suitable Applications

- 
MALL
- 
HALL
- 
HOTEL
- 
AIRPORT
- 
SPA



AVAILABLE SIZES
800x2400mm | 600x1200mm



Total Faces - 3



Technical Specification

GLAZED VITRIFIED TILES 9mm Thickness

Dimensions & surface Quality

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|-----------------------------------|---------------------------------|-----------------------------|--------------------|----------------------------|
| Deviation in length and width | ± 0.6% | ± 0.1% | ± 0.1% | ISO 10545:2/IS:13630 (P-1) |
| Deviation in thickness | ± 5% | ± 4% | ± 4% | ISO 10545:2/IS:13630 (P-1) |
| Deviation in Staightness of sides | ± 0.5% | ± 0.4% | ± 0.1% | ISO 10545:2/IS:13630 (P-1) |
| Deviation in Rectangualrity | ± 0.6% | ± 0.1% | ± 0.1% | ISO 10545:2/IS:13630 (P-1) |
| Deviation in Surface Flatness | ± 0.5% | ± 0.2% | ± 0.2% | ISO 10545:2/IS:13630 (P-1) |
| Surface Quality (%) | Minimum 95% | Minimum 95% | No visible defects | ISO 10545:2/IS:13630 (P-1) |
| Glossiness with Nano | Declared by manufacture | - | Above 90 | ISO 2813 (Glossy meter) |

Physical charactersitics

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|--|---------------------------------|---|--------------------|-----------------------------|
| Scratch Hardness of surface Moh's scale | Min. 3 | Min. 3 | Min. 3 | EN-101/IS:13630 (P-13) |
| Water absorption | ≤0.05% | Averages 0.08, Individual maximum 0.10% | <0.05% | ISO 10545:3/IS: 13630 (P-2) |
| Moisture Expansion | Nil | - | Nil | ISO 10545:10 |
| Surface Abrassion | Required | Required | PEI 2 - 4 | ISO 10545:7/IS:13630 (P-12) |

Mechanical charactersitics

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|--------------------|---------------------------------|---|--------------------|-----------------------------|
| Breaking strength | 1300 N | Min 1300 N | ≥ 1800 N | ISO 10545:4/IS: 13630 (P-6) |
| Modulus of rupture | >35 N/mm2 | Average 35, Individual minimum 32 | ≥ 35 N/mm2 | ISO 10545:4/IS: 13630 (P-6) |

Safety charactersitics

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|--|---------------------------------|-----------------------------|--------------------|---------------------------|
| Density | 2.20 gm/cc | Min 2.20 gm/cc | 2.25 gm/cc | DIN 51082/IS: 13630 (P-2) |
| Skid resistance (Friction coefficient) | ≥0.4 | - | ≥ 0.4 | ISO 10545:17 |

Thermo photo characteristic

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|--------------------------------------|---------------------------------|-----------------------------|-------------------------------------|-------------------------------|
| Thermal shock resistance | Resistant to 10 cycles | Min 10 cycles | Pass min 10 cycles | ISO 10545:9/IS: 13630 (P-5) |
| Co efficient of thermal expansion | 9×10-6K-1Max | 6×10-6K-1Max | <6×10-6K-1 Max | ISO 10545:8/IS:13630 (P-4) |
| Frost resistance | Resistant | Required | Need to comply with the standard | ISO 10545:12/IS: 13630 (P-10) |
| Color Resistance to UV light | Resistant | - | Resistant | DIN 51094 |

Chemical characteristics charactersitics

| Characteristic | Group Bla - ISO 13006/EN-176 | Group Bia IS :15622:2017 | Gruppo Nueva Value | Test According to |
|--|---------------------------------|-----------------------------|-------------------------|-----------------------------|
| Stain Resistance | Min class-3 | Required | Min conform to class-3* | ISO 10545:14 |
| Chemical Resistance HOUSE HOLD CHEMICAL & SWIMMING POOL SALT | min class-UB | Required | Conform to classes-UA* | ISO 10545:13/IS:13630 (P-7) |
| Chemical Resistance LOW CONCENTRATIONS ACID & ALKALIES | min class-ULB | Required | Conform to classes-ULA* | ISO 10545:13/IS:13630 (P-7) |
| Chemical Resistance HIGH CONCENTRATIONS ACID & ALKALIES | min class-UHB | Required | Conform to classes-UHA* | ISO 10545:13/IS:13630 (P-7) |

PACKING DETAILS

| Dimensions & Thickness (mm) | No.of tiles /box | Surface | Coverage Area | Box Weight |
|---------------------------------|---------------------|----------------------------------|---------------|-------------|
| 1200X2400X9 | 1 | Polished / HG / Smooth / Rough | 2.88 sqm | 62 kg (Avg) |
| 900x1800x9 | 2 | Polished / HG / Smooth / Rough | 3.24 sqm | 68 kg (Avg) |
| 800x1600x9 | 2 | Polished / HG / Smooth / Rough | 2.56 sqm | 54 kg (Avg) |
| 1200x1200x9 | 2 | Polished / HG / Smooth / Rough | 2.88 sqm | 62 kg (Avg) |
| 600x1200x9 | 2 | Polished / HG / Smooth / Roughed | 1.44 sqm | 31 kg (Avg) |
| 600x600x8.5 | 4 | Polished / HG / Smooth / Roughed | 1.44 sqm | 28 kg (Avg) |
| 300x600x8.5 | 6 | Polished / HG / Smooth / Roughed | 1.08 sqm | 21 kg (Avg) |

- Vitrified tiles have resistance to most of the stains/chemicals but, it is recommended to take due care while laying and for day-to-day maintenance.
- Resistance to acids & alkalies (Exception Hydrofluoric acids & its Compounds)
- Colours in the catalogue are as accurate as printing process allows. Please check actual tile sample before making the final selection
- Sizes mentioned in the catalogue are nominal sizes only.
- No claim will be entertained once the tiles are fixed.
- For better laying. Please follow the instructions on the packaging box.
- Please make sure to check the shade/finish with the sales agent/ dealer making the final purchase because there might be variation in actual finish that shown in the catalogue. The company will not bear any loss in such case.

Note

GruppoNueva
one group - one mind - one vision

Lakhdhirpur Road, Morbi 363642, Gujarat